

WÖHLER

Test Equipment Depot - 800.517.8431 - 99 Washington Street Melrose, MA 02176
TestEquipmentDepot.com



POWERFULLY TOUGH

Wöhler A 550 INDUSTRIAL

Portable Flue Gas Emissions Analyzer with superior accuracy

The Measure of Technology



Made in Germany



INDUSTRIAL



TUV
APPROVED

CO

100,000
ppm

NO_x
SO_x



ROBUST
HOUSING



7"
TOUCHSCREEN

PC

SOFTWARE



USB



BLUETOOTH®

12

MONTH
WARRANTY

Wohler A 550 INDUSTRIAL

Portable Flue Gas Emissions Analyzer with Capitalize Superior and Accuracy

As tough as cast iron, but as easy to operate as a smartphone – that's what Wohler's new Flue Gas Emissions Analyzer feels like in your hand. A tap of your finger on the Wohler A 550 INDUSTRIAL is all that is required to perform a complete analysis and inspection of boilers and burners. The Flue Gas Emissions Analyzer is designed to be used in tough industrial heat processes. The in-stack stainless steel sinter-filter probe protects the analyzer against heavy dust loads.

The new Wohler A 550 Industrial is our most advanced analyzer ever. The individual functions can be launched as intuitively as using a smartphone via the large 7" color touchscreen. And the brightly lit monitor can be read anywhere. The large screen, the clear arrangement and the graphical presentation of readings allow excellent readability.

Acquiring measurement values is as easy as could be. The analyzer is equipped with magnets, so you can attach it to any magnetic objects to work hands-free. The probe is equipped with a start/stop button to run or hold measurement readings. There are a number of interfaces available to transfer data: USB, Infrared and

Bluetooth®. And with the Wohler TD 100 Fast Thermal Printer you can print out the readings on-site.

The new battery-driven peltier cooler ensures both accurate NO_x and SO_x readings.

The optional stainless steel sinter-filter protects the device against industrial dust loads.

A broad variety of different sample probe lengths offers the opportunity to take emission measurements in difficult-to-reach locations.

To measure flue gas velocity and flow rate the Wohler A 550 INDUSTRIAL is equipped with a dual port digital pressure sensor. S-Tubes and Prandl-probes are available in different length and dimensions.

ADVANTAGES

- 7" color-touchscreen as intuitive to use as a smartphone
- NO_x and SO_x emissions measurement with 0.1 ppm resolution
- In-stack Sinter-filter probe for dust protection
- Battery-driven peltier cooler device - more than 4 h off-grid operation time
- High-power sample pump for differential pressures up to 300 mbar
- Built-in logger function with user selectable configuration

TECHNICAL DATA

Oxygen concentration (O₂) in flue gas

Display Volume % referenced to dry flue gas
Measurement principle..... Electrochemical sensor
Range 0.0 – 21.0 vol. %
Accuracy ± 0.3 vol. %

Carbon monoxide (CO 100,000) in flue gas

Display Volume ppm referenced to dry flue gas
Measurement principle..... Electrochemical sensor
Range 0 – 100,000 vol. ppm; resolution 1 vol. ppm
Accuracy ± 100 vol. ppm (< 1,000 vol. ppm),
otherwise 10 % of reading (with H₂ < 5 % of reading)

Nitric oxide concentration (NO) in flue gas

Display Volume ppm referenced to dry flue gas
Measurement principle..... Electrochemical sensor
Range 0 – 3,000 vol. ppm (continuously up to 1,000);
resolution 0.1 vol. ppm (< 1,000 vol. ppm),
otherwise 1 vol. ppm
Accuracy ± 5 vol. ppm (< 100 vol. ppm), otherwise 5 % of reading

Nitrogen dioxide concentration (NO₂) in flue gas

Display Volume ppm referenced to dry flue gas
Measurement principle..... Electrochemical sensor
Range 0 – 1,000 vol. ppm (continuously up to 200 vol. ppm);
resolution 0.1 vol. ppm
Accuracy ± 5 vol. ppm (< 100 ppm), otherwise 5 % of reading

Sulfur dioxide concentration (SO₂) in flue gas

Display Volume ppm referenced to dry flue gas
Measurement principle..... Electrochemical sensor
Range 0 – 5,000 vol. ppm;
resolution 0.1 vol. ppm (< 1,000 vol. ppm),
otherwise 1 vol. ppm
Accuracy ± 10 vol. ppm (< 200 vol. ppm), otherwise 5 % of reading

Differential pressure (P_d)

Display inWC
Measurement principle..... Semi-conductor diaphragm
Range 0.00 to ± 44.16 inWC; resolution 0.004 inWC
Accuracy 0.008 inWC (< 0.16 inWC), otherwise 5 % of reading

Flue gas temperature (T_g)

Display °F
Measurement principle..... Thermocouple (NiCr-Ni) (NiCr-Ni)
Range - 4 °F to 1,472 °F; resolution 32.18 °F
Accuracy 32-271.4 °F: ± 35.6 °F
271.4-1,472 °F: ± 1.5 % of reading

Combustion air temperature (T_A)

Display °F
Measurement principle..... Thermocouple (NiCr-Ni)
Range - 4 °F to 212 °F; resolution 32.2 °F
Accuracy ± 33.8 °F

Power supply Lithium-Ion, rechargeable battery 3.7 V, 5800 mAh,
charges via USB

Battery operating time Approx. 7 h (depends on operating status and display
illumination)

Storage temperature 4 °F to + 122 °F

Operating temperature + 41 – 104 °F to maintain stated accuracy

Weight 2.75 lbs

Dimensions 8.7" x 6.3" x 2.2" (without probe)

Length of cable-hose 67"

✂ Applications

- Expandable with up to 5 sensors
- For measurements: NO, NO₂, SO₂
- Probe for a variety of measurement tasks
- In-stack sinter-filter for heavy dust loaded samples

⚙ Functionality

- Simple to use: Switch on – read off – done
- Large, color touchscreen: Displays up to 14 measurement and calculation values
- Intuitive to operate via on-screen keyboard
- Calibrate in the flue gas pipe via a fresh air pump
- Graphic hot spot search

🔧 Safety / Reliability

- Effective dust and condensate protection
- 4-filter technology – easily accessible
- Analyzer and sensor diagnostics
- Sensor replacement – user-friendly
- Rechargeable battery operating time: more than 7 h with Lithium Ion power
- Hose assembly – robust and flexible

📁 Data management

- 1,000 measurement records
- Data transfer via USB, Bluetooth® or Infrared

❗ Approvals

- DIN EN 50379 Part 2



Battery-driven peltier cooler
removes condensate from the sample gas for accurate NOx and SOx measurements



Sinter-filter probe
removes dust (> 20 micron) from the sample gas to protect the analyzer against heavy dust loads

¹⁾ Except thermocouple, rechargeable battery and special sensors; for further information please read our warranty guidelines.

Kit and Accessories

Wohler A 550 INDUSTRIAL	Qty
Wohler A 550 INDUSTRIAL with O ₂ , NO, CO _{total} , NO ₂ , SO ₂ , Bluetooth®, USB- and IR, Hose 10 ft. and modular Flue Gas Probe 3 ft. with sinter filter, Ambient Temperature Probe (plug), USB-Charger with Micro-USB-Cable, Li-Ionen Battery, 1 Waterstopp Filter, 1 Coarse Filter, 25 Wadding Filters, Plastic Case	
	P/N 5996

Peltier cooler for NOx and SOx	Qty
USB Peltier Cooler for Wohler A 550 with battery and USB cable 10 ft. Portable Peltier Cooler with external mobile battery to remove condensate. Operational time up to 5h. To be used for accurate SO ₂ or NO ₂ flue gas analysis. Comes with: Wohler USB Peltier Cooler A 550, 10.000 mAh mobile battery pack, 10 ft. USB connection cable, Angle Adapter Peltier Cooler	
	P/N 4435

Probe with sinter-filter 20 micron	Qty
Flue Gas Probe 3 ft. with filter holder and stainless steel Sinter-filter to be used with Wohler A 550 INDUSTRIAL Flue Gas Emissions Analyzer	
	P/N 4189

Stainless steel Sinter-filter for Wohler A 550 INDUSTRIAL, replacement filter	P/N 4187
---	----------

Probes	Qty
Wohler A 550 Gas Probe 1.5 ft.	P/N 9614
Wohler A 550 Gas Probe 1 ft.	P/N 9622
Flue Gas Probe Wohler A 550 3 ft., with protective cap	P/N 9695
Wohler A 550 Air Temperature Probe 1 ft., with 1,7 m cable	P/N 5511
Wohler Velocity Probe Type S for Wohler A 550, to measure gas velocity	P/N 5579
Pitot Tube 3 ft., .2" diameter	P/N 9489
Pitot Tube 1.5 ft., .2" diameter	P/N 9488

Cones	Qty
Magnetic Holder for air temperature probes to stabilize the air temperature probe	P/N 6142

Clamping Cone for probes .3" diameter stainless steel, to stabilize the gas probe in the flue pipe	P/N 2494
---	----------

PTFE Cone for probes .3" diameter to stabilize air temperature probes in openings .3"- .5" diameter	P/N 2463
--	----------

Printer	Qty
Wohler TD 100 Thermal Fast Printer Infrared printer with 1 roll thermal paper and four batteries	P/N 4160

Thermal Paper 2" wide, 10 rolls for thermal printer Wohler TD 100 / TD 600	P/N 4145
---	----------

PC-Software	Qty
PC-Software Wohler A 550 on CD Languages EN, FR, IT, CZ, NL, CN for online measurements, diagram functions and export to MS Excel	P/N 4428

Consumables	Qty
Water Stop Filters pack with 3 pieces for Wohler A 400 / A 500 / A 600	P/N 9621

Coarse Filters pack with 5 pieces for Wohler A 500 / A 600	P/N 9632
---	----------

Wadding Filters pack with 150 pieces for Wohler A 400 / A 500 / A 600	P/N 4288
--	----------

