



AirChek **ESSENTIAL**

Low Price, Simple Operation Sample Pump

No operating manual needed

5 to 5000 ml/min

Just what you need!



Intuitive touch keypad operation

KEY FEATURES

- **Flows from 5 to 5000 ml/min**
 - 5 to 500 ml/min with low flow holder accessory
 - Multiple-tube sampling with low flow accessories
- **High back pressure compensation**
 - Up to 50 inches water at 2 L/min
- **Li-Ion battery — over 40-hour run times**
- **Corrects flow for changes in temperature and atmospheric pressure**
- **Bright running and status LEDs**
- **Displays elapsed time**
- **Flow fault and auto-restart**
- **Tough no-slip anti-static case**
- **Ultra-quiet**
- **Small and lightweight**
- **Convenient charging cradle**
 - Chain up to 5 cradles
- **Screen protection and security**
 - Protective cover
 - Screen lock-out feature

PERFORMANCE PROFILE

Flow Range	<ul style="list-style-type: none"> • Constant flow from 1000 to 5000 ml/min (5 to 500 ml/min requires low flow holder)
Compensation Range (back pressure capability)	<ul style="list-style-type: none"> • 5000 ml/min at 20 inches water back pressure • 4000 ml/min at 30 inches water back pressure • 3000 ml/min at 40 inches water back pressure • 2000 ml/min at 50 inches water back pressure • 1000 ml/min at 60 inches water back pressure
Power	<ul style="list-style-type: none"> • Removable rechargeable lithium-ion (Li-Ion), 7.4 V, 2.6 Ah, 19.2 Wh or AC using cradle
Run Time	<ul style="list-style-type: none"> • 40+ hours at 2000 ml/min,* 15+ hours at 5000 ml/min,* Indefinite run from charging cradle
Accuracy	<ul style="list-style-type: none"> • Flow control: ± 5% of set-point after calibration to desired flow • Atmospheric pressure: ± 0.3 in Hg • Temperature: ± 1.0 C
Display/Parameters	<ul style="list-style-type: none"> • B&W display, elapsed sampling time
User Interface	<ul style="list-style-type: none"> • Capacitive touch screen with locking option
Sound Level	<ul style="list-style-type: none"> • Average 51.7 dB at 3-ft (1-m) distance using a 37-mm, 0.8-µm MCE filter cassette
Tubing	<ul style="list-style-type: none"> • Requires ¼-inch ID tubing
Dimensions/Weight	<ul style="list-style-type: none"> • 4.1 x 3.7 x 2.8 in (10.4 x 9.4 x 7.1 cm), 19.4 oz (550 gm)
Certifications/Markings	<ul style="list-style-type: none"> • Intrinsic safety (SKC Cat. No. 220-3000 operated with SKC Battery Pack P75718) Class I, Groups A, B, C, D; Class II, Groups E, F, G; Class III, T4; Class I, Zone 0, AExia IIC T4 Ga; Exia IIC T4 Ga; -20°C ≤ Ta ≤ 45°C Ex II 1G; Exia IIC T4 Ga; IECEx UL 19.0100, UL22UKEX2351, UKCA 0843, DEMKO 19ATEX 2288, CE 0539 • Designed to meet ISO 13137:2013 • RoHS compliant

* Tested using 37-mm, 0.8-µm MCE filter with new pump and battery. Pump performance may vary.



ORDERING

Available as Cat. No.

220-3000	AirChek Essential Pump only
220-3000-S	Starter Pump Kit
220-3000-K	Single High Flow Pump Kit
220-3000-K3D	3-pack High/Low Flow Pump Kit
220-3000-K5	5-pack High Flow Pump Kit

"Pump only" requires charging cradle and power supply that are included in kits. See more at www.skcinc.com.

Recommended Calibrator[†]

375-0550N	chek-mate with NIST standard traceable calibration certificate
375-0550	chek-mate with UK standard traceable calibration certificate

[†]Available with ISO standard traceable certificate. Contact SKC for details.

Recommended Accessories

210-500	Low Flow Adapter Kit
224-911	Protective Pouch

For ordering details and additional accessories, visit www.skcinc.com.

Selection Guide

AirChek	AirChek ESSENTIAL	AirChek TOUCH	AirChek CONNECT
Listed Intrinsically Safe	•	•	•
Operation	Touch keypad	Color touch screen	Touch screen
Programmable		•	•
PC Compatible – Download History		•	•
Bluetooth™			•
Mobile App			•
Compensates for Changes in Temperature and Atmospheric Pressure	•	•	•
Flow Fault/Auto-restart	•	•	•